



Epson WorkForce Pro EM-C800

- PrecisionCore Heat-Free Technology – simple, smart and clean solution that delivers outstanding quality with low waste
- Energy efficient – low power consumption
- Powerful business productivity – print speed of 25 ISO ppm¹ (mono/colour); fast first page out time of 4.8 sec and zero warmup time
- Engineered for reliable performance – recommended monthly print volume of up to 5,000 pages
- Remarkable image quality – DURABrite™ Ultra, replaceable ink pack system (RIPS) delivers vivid colour and crisp black text
- Robust security – full suite of advanced security features
- Compatible with Epson Solutions Suite and industry-leading third-party solutions – Epson Open Platform for seamless workflow integration
- Intuitive operation – 4.2" colour touchscreen
- Minimal user intervention – replaceable ink pack system with extra high-capacity packs lets you print up to 50,000 ISO pages mono / 20,000 ISO pages colour²

Epson WorkForce Pro EM-C800

Product Specifications	
PRINT	
Printing technology	PrecisionCore 4S printhead 4-colour inkjet
Maximum print resolution	4800 x 1200 optimised dpi
Print speed ¹	25 ISO ppm (mono), 25 ISO ppm (colour)
MOBILE PRINTING AND SCANNING	
Epson Connect Solutions	Epson Email Print, Epson Remote Print, Epson Smart Panel App
FPOT (First page out time)	4.8 s
Recommended duty cycle per month	5,000 (maximum)
Compatible paper weight	64 gsm to 256 gsm
Other	AirPrint [®] , Mopria [®] Print Service, Microsoft [®] Universal Print, Fire [™] OS
COPY	
Copy speed flatbed ³	22 ISO cpm (mono), 22 ISO cpm (colour)
Maximum copy size	A4
Input copy resolution (dpi)	Maximum 600 x 1200
Copy features	Auto 2-sided, preview, resize, ID copy, collate, adjustable copy density, remove punched holes, remove shadows
SCAN	
Scanner type	Colour flatbed / auto 2-sided ADF
Scanner sensor	Colour CIS line sensor
Hardware resolution	Maximum 1200 x 2400 dpi
Optical resolution	1200 dpi
Maximum resolution	9600 dpi interpolated
Scanner speed ⁴	ADF simplex 30 ipm / duplex 60 ipm
Scanner features	Scan to PC via Document Capture Pro, scan to cloud ⁵ , scan to email, scan to network folder, memory device, password protected PDFs
FAX (OPTIONAL)	
Type	Mono-and-white and colour
Transmission speed	Up to 33.6 kbps / approx. 3 sec / page
Receive memory	Up to 550 pages
Speed dial numbers	Up to 2,000
Fax features	PC fax, fax to email, memory reception, auto redial, speed dial, fax to folder, address book, broadcast fax, fax preview
PAPER HANDLING	
Paper formats	A4 (210 mm x 297 mm), A5 (148 mm x 210 mm), A6 (105 mm x 148 mm), B5, B6, C4 (envelope), C6 (envelope), DL (envelope), No. 10 (envelope), letter, legal, 90 x 130 mm, 100 x 150 mm, 130 x 180 mm, 16:9, HLT, EXE, user defined
Input paper capacity	250 sheets plain paper (250 sheets plain paper x 1 tray); rear feed: 80 sheets (1,830 sheets total with three optional 500-sheet paper trays); No. 10 envelopes
Output tray capacity	150 sheets
Automatic 2-sided scan / copy / fax	Yes
CONNECTIVITY	
Standard connectivity	Hi-speed USB (compatible with USB 2.0 specification), Wireless LAN IEEE (802.11 b/ g/n/ac), Wired Ethernet (1000 Base-T/100 Base-TX/10 Base-T), Wi-Fi Direct [®]
Operating systems	Windows [®] 11, Windows 10 (32-bit, 64-bit), Windows 8, 8.1 (32-bit, 64-bit), Windows 7 (32-bit, 64-bit), Windows Server [®] 2008, 2012 [®] – Windows Server 2016, 2019, 2022 [®] , Mac [®] OS X [®] 10.9.5 – macOS [®] 14.x ⁷
GENERAL	
Display	4.2" colour touchscreen
Temperature	Operating: 10°C to 35°C, Storage: -20°C to 40°C
Noise level	36 dB
Rated voltage / frequency	AC 100 V – 240 V / 50 Hz – 60 Hz
Power consumption (approximate)	Standalone copy printing: 30 W Ready mode: 13.8 W Sleep mode: 1.1 W TEC rating: 0.18 kWh / week
Weight and dimensions (W x D x H)	Main unit: 21.3 kg, 425 mm x 535 mm x 413 mm
Software available ⁸	Epson printer driver, PCL 5 driver emulation ⁹ , PCL 6 driver emulation ⁹ , Adobe [®] PostScript [®] 3 [™]
Epson Solutions Suite	Epson Device Admin, Epson Print Admin, Epson Print Admin Serverless, Epson Remote Services

1 Mono and colour print speeds are measured in accordance with ISO/IEC 24734. Actual print times will vary based on factors including system configuration, software and page complexity. For more information, visit www.epson.com.au/printspeed/

2 Replacement ink pack yields are estimated based on ISO/IEC 24711 test in default mode printing continuously. Ink pack yields vary considerably for reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently or predominantly with one ink colour.

3 Mono and colour copy speeds are determined in accordance with ISO/IEC 29183. Actual copy times will vary based on factors including system configuration, and page complexity. For more information, visit www.epson.com.au/printspeed/

4 Based on 200 dpi, letter-size (215.9 mm x 279.4 mm), in mono or colour.

5 Requires an internet connection, a free Epson Connect account and a destination email address or cloud storage account. For a list of supported cloud services, visit www.epson.com.au/connect

6 Only printing and scanning are supported under Windows Server OS.

7 Some applications and/or functions may not be supported under Mac OS X.

8 Internet access is required to download and install drivers and software.

9 Not all media types are supported for PCL printing.

Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice with customers recommended to check with the Epson AU/NZ websites for latest details.

Epson CoverPlus

Fast. Reliable. Professional

Epson Australia Pty Ltd
www.epson.com.au

Epson New Zealand
www.epson.co.nz

10/2024

ABN: 91 002 625 783

EPSON