

## **Epson WorkForce Pro EP-C800**

- PrecisionCore Heat-Free Technology simple, smart and clean solution that delivers outstanding quality with low waste
- Energy efficient low power consumption
- Powerful business productivity print speed of 25 ISO ppm¹ (mono / colour); fast first page out time of 4.8 sec and zero warmup time
- Engineered for reliable performance recommended monthly print volume of up to 5,000 pages
- Remarkable image quality DURABrite™ Ultra, replaceable ink pack system (RIPS) delivers vivid colour and crisp black text
- Robust security full suite of advanced security features
- Compatible with Epson Solutions Suite and industry-leading third-party solutions – Epson Open Platform for seamless workflow integration
- Intuitive operation 2.4" colour touchscreen
- Minimal user intervention replaceable ink pack system with extra high-capacity packs lets you print up to 50,000 ISO pages mono / 20,000 ISO pages colour<sup>2</sup>

## **Epson WorkForce Pro EP-C800**

Draduct Charifications			
Product Specifications  PRINT		CONNECTIVITY	
Printing technology  Maximum print resolution  Print speed¹  MOBILE PRINTING	PrecisionCore 4S printhead 4-colour inkjet 4800 x 1200 optimised dpi 25 ISO ppm (mono), 25 ISO ppm (colour)	Standard connectivity	Hi-speed USB (compatible with USB 2.0 specification), Wireless LAN IEEE Standard Connectivity: Wireless (802.11 b/g/n/ac), Wi-Fi Wired Ethernet (1000 Base-T/100 Base-TX/10 Base-T), Wi-Fi Direct®
Epson Connect Solutions FPOT (First page out time)	Epson Email Print, Epson Remote Print, Epson Smart Panel App 4.8 s	Operating systems	Windows® 11, Windows 10 (32-bit, 64-bit), Windows 8, 8.1 (32-bit, 64-bit), Windows 7 (32-bit, 64-bit), Windows Server® 2008, 2012³ – Windows Server 2016, 2019, 2022³, Mac®OS X® 10.9.5 – macOS® 14.x⁴
Recommended duty cycle per month	5,000 (maximum)	GENERAL Display	2.4" colour touchscreen
Compatible paper weight	64 gsm to 256 gsm	Temperature	Operating: 10°C to 35°C, Storage: -20°C to 40°C
Other	AirPrint®, Mopria® Print Service, Microsoft® Universal Print, Fire™ OS	Noise level Rated voltage / frequency	37 dB AC 100 V – 240 V / 50 Hz – 60 Hz
PAPER HANDLING		natou tottage / noquency	Standalone copy printing: 24 W
Paper formats	A4 (210 mm x 297 mm), A5 (148 mm x 210 mm), A6 (105 mm x 148 mm), B5, B6, C4 (envelope), C6 (envelope), DL (envelope), No. 10 (envelope), letter, legal, 90 x 130 mm, 100 x 150 mm, 130 x 180 mm, 16:9, HLT, EXE, user defined	Power consumption (approximate)	Ready mode: 7 W Sleep mode: 1.1 W TEC rating: 0.16 kWh / week
		Weight and dimensions (W x D x H)	Main unit: 17.6 kg. 425 mm x 535 mm x 413 mm
Input paper capacity	250 sheets plain paper (250 sheets plain FPOT (First page out paper x 1 tray); Rear Feed: 80 sheets (1,830	Software available <sup>5</sup>	Epson printer driver, PCL 5 driver emulation <sup>6</sup> , PCL 6 driver emulation <sup>6</sup> , Adobe <sup>®</sup> PostScript <sup>®</sup> 3 <sup>™</sup>
Output tray capacity	sheets total 150 sheets	Epson Solutions Suite	Epson Device Admin, Epson Print Admin, Epson Print Admin Serverless, Epson Remote Services

Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice with customers recommended to check with the Epson AU/NZ websites for latest details.





<sup>1</sup> Mono and colour print speeds are measured in accordance with ISO/IEC 24734. Actual print times will vary based on factors including system configuration, software and page complexity. For more information, visit www.epson.com.au/printspeed/

<sup>2</sup> Replacement ink pack yields are estimated based on ISO/IEC 24711 test in default mode printing continuously. Ink pack yields vary considerably for reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently or predominantly with one ink colour.

<sup>3</sup> Only printing supported under Windows Server OS.

<sup>4</sup> Some applications and/or functions may not be supported under Mac OS X.

<sup>5</sup> Internet access is required to download and install drivers and software.

<sup>6</sup> Not all media types are supported for PCL printing.