Optional heavy roll support

# Epson SureColor F11060/F11060H

- Cost-effective fabric and soft signage production at up to 255 m^2/hr
- Quality imaging on media up to 76" (1950 mm) wide
- Dual 40/60 L bulk ink supply system with hot swap
- Epson UltraChrome® DS ink delivers an exceptional gamut using just 4 colours
- 6-colour F11060H supports additional OrVi, LcLm, or Fluro ink
- Advanced platen and high-precision feed management for efficient high-quality roll-to-roll production on the widest range of media with optional heavy roll support
- Latest Epson PrecisionCore™ printheads for outstanding results at the highest speeds
- Oeko-Tex™ certification guarantees the fabric's safety for adults, children & infants[1]
- Epson Cloud Solution PORT for remote monitoring, management and service support
- Comprehensive and flexible service with cover extendable up to FIVE years with optional user self-replacement of selected key components, including printheads[2]

Epson SureColor Fabric Range SC-F11060/H
76" High-speed Roll-based Dye Sublimation

Product Specifications

PRINT TECHNOLOGY

Printhead	4 x 4.7" PrecisionCore™ Micro TFP (6 with F11060H), Variable Sized Droplet Technology & Precision Dot Technology, ink-less nozzle status monitoring, auto recovery & self-cleaning, optional user self-replacement[3]
Max resolution	1,200 x 1,200 dpi
Min droplet size	3.8 pl

INK SYSTEM

Ink family	Epson Ultrachrome® DS
Ink type	Dye sublimation (high-density black)
Supply	Dual 3/10 L with hot swap (F11060: CYMK, F11060H: CYMKLcLm, CYMKFyFp or CYMKOrVi)

PERFORMANCE[4]

Fast fabric (F11060/H)	255/246 m²/hr, 1.1 pass (300 x 600 dpi)
Apparel (F11060/H)	150/144 m²/hr, 2.1 pass (600 x 600 dpi)
Soft signage (F11060/H)	103/99 m²/hr, 3.1 pass (600 x 600 dpi)

MEDIA SUPPORT

Format (standard roll)	Single roll 250 mm max diameter, 60 kg max weight, 1 mm max thickness, 914.4 ~ 1950 mm width (2" or 3" core)
Format (heavy roll)	500 mm max diameter, 300 kg max weight, 1 mm max thick, 3" core[5]
Print margins (min)	7 mm L/R (14 mm with edge guides), 5 mm top / bottom

OPERATION

Control panel	9" colour LCD with in-built help
Included software	Comms Driver, Epson Net Setup, Net Config & Print, Edge Dashboard, Edge Print Pro, & Epson Cloud Solution PORT
Interface	USB 3.0 & Ethernet / 1000Base-T
Memory	155 GB
Media dryer	Dual front & back with adjustable temp: 0 ~ 110ºC

ENVIRONMENTAL

Operational temp	10 - 35ºC (18 - 28ºC recommended)
Operational humidity	20 - 80% (no condensation, 40 - 60% recommended)
Power supply	2 x 16 A 220 V - 240 V, 50 - 60 HZ
Power consumption	F11060H printer: 4.4 KW operating / 230 W standby (approx)
Operating noise	59 dB
Operating space (W x D x H)	6 x 4 x 2 m (recommended)

PHYSICAL

Dimensions (W x H x D, no ink)	F11060: 4,587 x 1,886 x 1,303 mm, 587 kg
F11060H: 4,988 x 1,886 x 1,303 mm, 781 kg
Heavy roll unit (add): 0 x 0 x 437 mm, 208 kg

CONFIGURATIONS & OPTIONS[2, 3]

SCF110601Y	4c printer with CoverPlus 1-yr onsite service
SCF110603Y	4c printer with CoverPlus 3-yr onsite service
SCF110605Y	4c printer with CoverPlus 5-yr onsite service
SCF11060H1Y	6c printer with CoverPlus 1-yr onsite service
SCF11060H3Y	6c printer with CoverPlus 3-yr onsite service
SCF11060H5Y	6c printer with CoverPlus 5-yr onsite service
C12C938461	Standard roll & reel units
SCF11SOJRE	Heavy roll and standard reel units

CONSUMABLES

C13S210071	Replacement waste tank
C13S210065	Replacement head wiper roll
C13S210103	Cleaning kit
C13T43B140~440	3 L CYMK UltraChrome ink boxes
C13T43B540/640	3 L Lc/Lm UltraChrome ink boxes
C13T43B740/840	3 L Fy/Fp UltraChrome ink boxes
C13T43H140~440	10 L CYMK UltraChrome ink boxes
C13T43H540/640	10 L Lc/Lm UltraChrome ink boxes
C13T43H740/840	10 L Fy/Fp UltraChrome ink boxes
C13T43HA40/D40	10 L Or/Vi UltraChrome ink boxes

WHAT'S IN THE BOX[6]

Printer with dryer and ink supply system, 2 x 3 L CYMK ink set, 1 x reusable 4 L waste tank, 1 x head wiper roll, 1 x cleaning kit, Epson Edge Print PRO & Cloud Solution PORT service.

1 Epson dye sublimation inks used in this printer meet the needs of Oeko-Tex Eco Passport safety standard when applied and affixed to appropriate fabric. For further details on this standard, please visit www.oeko-tex.com/ecopassport
2 The printer is supplied with a 90-day warranty that covers the print mechanism (including printheads) and ink system. Optional onsite CoverPlus is also available. Visit www.epson.com.au/coverplus or www.epson.co.nz/coverplus for full details.
3 This model supports user replacement of selected components, subject to Epson Cloud Solution PORT registration and operator training.
4 Figures presented are print speeds only. Actual production times will vary depending on a range of factors including print mode, computing platform, print application/RIP, file type/format/size, networking, and sublimation method. Effective resolution with half tone application is 300 x 300 dpi.
5 The take-up reel is limited to maximum 250 mm diameter and 60 kg weight. Please contact Epson if a heavy roll take-up is required.
6 Ink and media may be supplied in additional boxes. Operation will require installation of an appropriate power supply and connection to a network with Internet access. Typically, acquiring a calendar press is also necessary. Some software components will need to be downloaded from the appropriate Epson website. Important: Not all software is Mac compatible (check website for details).

Compact double-sided drying system

Advanced media set-up with automatic self-adjustment

OEKO TEX® ECO PASSPORT NEP 1902 Nissenken www.oeko-tex.com

Epson Cloud Solution PORT

Epson CoverPlus
Fast. Reliable. Professional

EPSON