

Epson SureColor F9460 / F9460H

- Designed for roll-based fabric & soft signage production at up to 60 m²/hr
- Epson UltraChrome® HDk DS ink enables an exceptional gamut using just 4 colours
- Optional Florescent Ink (F9460H) enables sublimated product with maximum impact
- Advanced image processing for superior print quality and fine gradation
- Dual Epson PrecisionCore[™] print heads with active nozzle status monitoring and auto self-cleaning for sustained production with minimum maintenance
- Automatic Tension Control (ATC), high-precision Auto Take-Up (ATU), remote status notification, and Continuous Ink Supply System (CISS) for cost-effective high-volume roll-to-roll production
- Oeko-Tex[™] certification ensures fabric is safe for adults, children & infants⁴
- Supplied complete with Epson Edge Print and Accounting Software
- Comprehensive single source warranty with on site cover extendable up to FIVE years³


Epson SureColor Fabric Range SC-F9460 64" High Speed Roll Based Dye-Sub System

Product Speci	fications		
SIZE		ENVIRONMENTAL	
Max Print Width	64 inch (1625.6 mm)	Operational Temp	15~35°C (15~25°C recommended)
PRINT TECHNOLOGY		Operational Humidity	20~80% (no condensation,40~60% recommended)
	Dual PrecisionCore [™] TFP with advanced Variable	Power Supply	2 X 5A 220 V ~240 V, 50 HZ - 60 HZ
Print Head	Sized Droplet technology, nozzle status monitoring,	Power Consumption	570W Operating / 340W Standby (Heater On) /14 W Sleep
	and auto self cleaning system	Operating Noise	54 dB
Print Modes	Uni & Bi-directional	PHYSICAL	
Configuration	2/4 x 360 Nozzles per colour	Dimensions	2620 x 1332 x 934 mm (WxHxD)
Max Resolution	720x1440 dpi	Weight	290 kg (with MSS & CISS, no ink)
Min Droplet Size	4 pl	Packaging	Printer: 3.2 x 1.1 x 1.1 m, 390 kg
INK SYSTEM			MSS & CISS: 3.1 x 1.1 x 0.6 m, 100 kg
Ink Family	Epson Ultrachrome® DS & DS6	WHAT'S IN THE BOX ²	
Ink Type	Dye Sublimation	Printer, Media Supply System (MSS) with ATU, CISS, 1 x Starter Ink Set, 1 x reusable 2 L Waste Tank, 1 x Maint Kit, 1 x Head Clean Set, 1 x 64" Roll of Epson Multi-Purpose Transfer Paper, Installation/ Guide, Utility & User manual (CD), Epson Edge Print (CD).	
Ink Set	4c F9460: Dual CYM + Dual High Density Black) 6c F9460H: Dual CYMK + Dual HDk + Single FpFy		
Supply	8/10 x 1.5 L Continuous Ink Supply System (CISS)		
PERFORMANCE ¹		CONFIGURATION OPTIONS ³	
4c Max Speed	108.6 m2/hr 1 Pass (360 x 720 dpi all models)	SCF94601Y	4c Printer with 1YR Warranty
4c Production	60.1 m2/hr 2 Pass (720 x 720 dpi all models)	SCF94603Y	4c Printer with CoverPlus 3YR on-site service
4c Quality Production	44.1 m2/hr 3 Pass (720 x 720 dpi all models)	SCF94605Y	4c Printer with CoverPlus 5YR on-site service
4c High Quality	29.9 m2/hr 4 Pass (720 x 720 dpi all models)	SCF9460H1Y	6c Printer with 1YR Warranty
4c Max Quality	13.3 m2/hr 8 Pass (720 x 1440 dpi all models)	SCF9460H3Y	6c Printer with 3YR on-site service
6c Fast Production	32.1m2/hr 4 Pass (720 x 720 dpi 9460H only)	SCF9460H5Y	6c Printer with 5YR on-site service
6c Production	21.9m2/hr 6 Pass (720 x 720 dpi 9460H only)	CONSUMABLES	
6c Quality Production	15.8m2/hr 8 Pass (720 x 720 dpi 9460H only)	C13T724000	Replacement Waste Tank
6c Max Quality	9m2/hr 12 Pass (720 x 720 dpi 9460H only)	C13S210063	Maintenance Kit
MEDIA SUPPORT		C13S210051	Head Cleaning Set
Roll Format	Single Roll, 250 mm max diameter, 45 kg max weight,	C13S090013	Cleaning Sticks
	0.04-1 mm thick (45 gsm or greater), 300-1625.6 mm width	C12C890891	Cleaning Wipes
Print Margins	5 mm min (10 mm with media holding plate)	C13T46D840	6 x 1.1 L High Density Black UltraChrome DS Ink Refills
OPERATION		C13T46D240	6 x 1.1 L Cyan UltraChrome DS Ink Refills
Control Panel	2.5" Colour LCD with in-built help	C13T46D340	6 x 1.1 L Magenta UltraChrome DS Ink Refills
Included Software	Communications Driver, EpsonNet Setup, EpsonNet Config & Print utilities, Epson Control Dashboard Epson Accounting Tool & Edge Print	C13T46D440	6 x 1.1 L Yellow UltraChrome DS Ink Refills
		C13T46D540	2 x 1L Fluro Pink Ultrachrome DS6 Ink Refills
		C13T46D640	2 x 1L Fluro Yellow Ultrachrome DS6 Ink Refills
Interface	USB 2.0 & Ethernet 100Base-TX/1000Base-T	Performance figures are printer speeds only for output designed to be used for fabric application; actual production times will vary a range of factors including output application, print mode, computing platform, print application/RIP, file type/ format/size and networking configuration. Two HDk starter ink packs are included with both models, the F9460H ships with an additional Fluro starter pack. The independent sourcing of a calend press and ancillary heater/blower will generally also be required. Some software components including the Epson Accounting Tool will need to be	
Memory	512 MB Main + 128 MB Network		
Media Output Heater	Selectable Off, 15-35°C		













reproduction with optional Fluro



High capacity 15 / 18L CISS. Tanks can be refilled while printing continues



Advanced Self-monitoring and Self-Cleaning systems



downloaded from the appropriate Epson Website. Important: not all software is Mac compatible (check website for details).

consumables; please refer to the relevant Epson website for details

Efficient production with single operator media loading.



Advanced UltraChrome DS ink ships in cost-effective 1/1.1L packs

Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and are trademarks of their respective owners; Epson disclaims any and all rights. Specifications are subject to change without notice. Visit www.epson.com.au or www.epson.co.nz for the latest information.

